

Digital clock

Digital clock

Cristalys Ellipse

Description:

- ▶ Indoor clock with liquid crystal display (LCD).
- ▶ Hour and multilingual date display, with temperature.
- ▶ Extra flat casing.
- ▶ Readability 20 metres, angle of vision 160°.
- ▶ Power supply with 4 LR 14 batteries for an autonomy over 3 years or PoE (Power over Ethernet) for NTP version.
- ▶ Versions: independent quartz, radio synchronised (FI or DCF), DHF receiver, impulse slave movement, IRIG B/AFNOR coded time receiver or NTP receiver.



Technical features:

- ▶ Eco function providing energy savings through switching off display between 23.00 and 6.00.
- ▶ Multifunctional display.
- ▶ Display in a choice of 12 languages.
- ▶ Temperature display from -25°C to +70°C or -13°F to +158°F.
- ▶ Selection °C or °F in the menu. Display resolution: 1°C. Accuracy: ±0.5°C. Offset adjustment, possible from -9.5° to +9.5° in 0.5° steps.
- ▶ 12 or 24 hour display mode.
 - ▶ Pre-programmed automatic summer/winter time changeover and perpetual calendar with multi-time zones.
- ▶ Permanent data saving.
- ▶ Accuracy of the time quartz base: 0.2 second/day.
- ▶ ABS casing, IP40, IK02.
- ▶ Silent operation.
- ▶ Programming and time setting through 2 buttons.
- ▶ Absolute time accuracy with optional radio synchronisation.
- ▶ Power supply with 4 LR14 (C) batteries for an autonomy over 3 years or PoE (Power over Ethernet) for NTP version.
- ▶ PoE consumption: 2.5 W maximum; Class 0 device.
- ▶ Optional very low voltage power supply from 6 to 24V AC/DC (or external 230V).
- ▶ Operating temperature: from 0 to 50°C.
- ▶ Humidity: 80% at 40°C.
- ▶ Weight: 1,4 Kg.



**4 casing colours:
aluminium,
champagne,
burgundy, white**

Multifunctional clock:

Possibility for fixed or alternate display on the bottom display line:

- ▶ Multilingual date.
- ▶ Numerical date.
- ▶ Indoor ambient temperature.
- ▶ Day number (Julian) and week number.
- ▶ Second counter.
- ▶ Site or city or company name or message (up to 7 characters).



**France Inter or
DCF transmitter**

Cristalys Ellipse references

▶ Independent quartz	938 311
▶ Radio synchronised France Inter	938 321
▶ Radio synchronised DCF	938 323
▶ Slave movement on impulses or IRIG B/AFNOR receiver	938 331
▶ Slave movement on impulses or IRIG B/AFNOR receiver (very low voltage)	938 332
▶ DHF radio receiver	938 341
▶ DHF radio receiver (very low voltage)	938 343
▶ NTP PoE receiver	938 363

Add to the reference: A for aluminium casing colour, B for white, C for champagne, D for burgundy.



Digital clock

Digital clock

Cristalys Ellipse



Cristalys Ellipse
on table support



Cristalys Ellipse
on double sided
bracket

Movements and synchronisation:

Quartz movement

- ▶ The clock is totally independent, the time information is provided by its own time basis.
- ▶ Automatic summer/winter time changeover.

DHF movement

- ▶ The clock is radio-synchronised by a DHF transmitter.
- ▶ Automatic summer/winter time changeover.

FI or DCF Radio synchronised movement

- ▶ The clock is independent, the time information is provided by its own time basis which is corrected, in case of drift, by comparison to the FI or DCF transmitter signal.
- ▶ The radio synchronisation permit to display the time with perfect accuracy.
- ▶ Automatic summer/winter time changeover.

IRIG B/AFNOR coded time receiver

- ▶ The coded time distribution consist in transmitting a complete time message each second: the setting on time of the receivers is realised automatically and quickly as soon as they are connected to the time distribution line.
- ▶ The IRIG B/AFNOR coded time does not transmit interference and is insensitive to other electrical interference.

24V minute impulses receiver movement

- ▶ The receiver clocks are connected to a distribution line and activated by means of electrical impulses transmitted every minute by the master clock.



NTP PoE receiver

- ▶ A NTP time server sends UTC time periodically on the Ethernet network. The clocks pick up the time messages, apply the relevant time zone and set themselves automatically to local time. PoE power is supplied to the clock through the network via the RJ45 plug.

Norms:

- ▶ Norm NF EN50081-1: generic emission standard.
- ▶ Norm NF EN50082-1: generic immunity standard.
- ▶ Norm NF EN60950: safety of information technology equipment.

Dimensions in mm



Options :

- | | |
|---|---------|
| ▶ Wall support (supplied with each Cristalys clock) | 202 271 |
| ▶ Table support | 938 902 |
| ▶ Double sided bracket for wall or ceiling mounting | 938 901 |
| ▶ Double sided bracket for wall or ceiling mounting (long length) | 938 905 |
| ▶ Single or double sided bracket specific length for wall or ceiling mounting | 938 908 |
| (Please specify on the order the fixing mode (wall or ceiling) and the length between the top of the clock and the fixing point). | |
| ▶ Support for very low voltage power supply | 938 907 |
| ▶ Plug-in mains adapter 230V/15V (Capacity : 20 clocks) | 938 912 |

